

# Tool & Product Update

## MARKET RELEASE

### 2581 - A2581 - 2582 - A2582 - 2583 - A2583 HYDRAULIC INSTALLATION TOOLS

This new lightweight tool family retains the durability and compact features of other popular 2500 tools! Offered in both electric- and air-trigger versions, and a variety of hose lengths, these new models feature improvements such as:

- Nylon insulating handle which protects hands from heat buildup
- Ergonomic and reliable trigger
- Hydraulic hose and cable connections enclosed in new handle design for protection of fittings
- Reduced weight of tool:  
2581/A2581 (2580)- *appx 1 lb reduction*  
2582/A2582 (2502)- *appx .4 lb reduction*  
2583/A2582 (2503)- *appx .8 lb reduction*
- Internal components (piston, glands, back caps) of these new tools are interchangeable with previous models if necessary
- Common handle assembly is used for all three tools



#### PRODUCT SPECIFICATIONS

TOOL	2581/A2581	2582/A2582	2583/A2583
<b>STROKE</b> inch (cm)	.937 (2.38)	.750 (1.91)	1.5 (3.81)
<b>CAPACITY@</b> 5700 psi (393 bar)	8240 lbs. (36.65 kN)	7500 lbs. (33.36 kN)	7500 lbs. (33.36 kN)

For more information or to order, please contact your local distributor or call direct: **Alcoa Fastening Systems**

1 Corporate Drive  
Kingston, NY 12401  
800-278-4825

November 13, 2014  
**PB621**

